

# Pesticides Cabinet

**WA810120G**



It has acquired FM & CE Certification and is in strict comply with FM Approval Standard for Storage Cabinets (Flammable and Combustible Liquids) Class Number 6050, OSHA 29 CER 1910.106 of American Occupational Safety and Health Administration, NFPA CODE30 of American National Fire Protection Association and Hazardous Chemicals Control Ordinance of State Bureau of Safe Production Supervision and Administration

**SYSBEL Safety Cabinets for Pesticides for storing insecticides, pesticides, disinfectors and other chemicals. Suitable for lawn care, golf course, farms, etc.**

1. Double wall construction with 38mm insulating air space for fire resistance.
2. Over 1.2mm thick, fully welded, construction holds squareness for longer life, offering greater protection in a fire.
3. 5.3cm leak tight sump at the bottom of cabinet's maximally catches incidental drips.
4. Door can be fully opened to 180°, easy to operate, three-point latch with a manual lock for better security.
5. Standardized warning label is highly visible and anti-corrosive.
6. Unique spill-catcher shelves catch incidental drips and adjust on 6cm centers.
7. Durable & chemical resistant, lead-free powder coat inside and outside cabinet, reduce effects of corrosion and humidity.
8. In terms of OSHA, on outside side panel, there is built-in grounding static connector for easy grounding.



China's first certified by FM



**Pesticides Cabinet WA810120**

| Volume (Gal/L) | Certification | Door type           | Ext dimension (H×W×D/cm) | Packing dimension (H×W×D/cm) | Adjustable Shelves(Pcs) | Shelf Loading Weight(Kgs.) | N.W. (Kgs.) | G.W. (Kgs.) | Model     |
|----------------|---------------|---------------------|--------------------------|------------------------------|-------------------------|----------------------------|-------------|-------------|-----------|
| 12/45          | FM, CE        | Single Door/ Manual | 89x59x46                 | 108x70x57                    | 1                       | 50                         | 44.6        | 56          | WA810120G |


**WA810120G**



**Product details**




18Ga(1-mm)quality galvanized steel  
Unleaded coating with polish surface,  
which is corrosion and moisture proof




Fireproofing vents to effectively reduce  
the concentration of volatile substances,  
and prevent fire hazards. Special spill-  
proof shelves to avoid chemical leakage  
by accident.



Adjustable shelves with anti-  
leakage design



The cabinet has three-point linkage lock,  
and the door can open 180°  
Two person management in line with  
Hazardous Chemicals Control Ordinance  
(December 1st, 2011 Version)



Shelf bracket welded on both  
sides of cabinet



FM Approved Anti-Static  
Device: Conductor grip combine  
the equipment with the cabinet to  
conduct the static to earth, thus to  
prevent fire accident



The three-point bullets: Anti-static design  
structure

