

Horizontal Drum Storage Cabinet

WA810550H



It has acquired CE Certification and OSHA 29 CER 1910.106 of American Occupational Safety and Health Administration, NFPA CODE30 of American National Fire Protection Association and Hazardous Chemicals Control Ordinance of State Bureau of Safe Production Supervision and Administration

SYSBEL's horizontal drum storage cabinets are designed for house drum ,including tracks to guide drum into position and Drum Cradle . Follow the design rules of flammable liquid storage cabinet . Meet the specification of OSHA29CFR 1910.106 and NFPA CODE 30. Form a complete set of slippery course to guide the oil drum bracket cart in and out.

- 1.Double-wall construction with 38mm insulating air space for fire resistance.
- 2.Over 1.2mm thick, fully welded,construction holds squareness for longer life, offering greater protection in a fire.
- 3.5.3cm leak tight sump at the bottom of cabinet's maximally catches incidental drips.
- 4.Door can be fully opened to 180°, easy to operate, three-point latch with a manual lock for better security.
- 5.Standardized warning label is highly visible and anti-corrosive.
- 6.Unique spill-catcher shelves catch incidental drips and adjust on 6cm centers.
- 7.Durable&chemical resistant,lead-free powder coat inside and outside cabinet,reduce effects of corrosion and humidity.
- 8.2inches vents with integral flame arresters in both sides of every cabinet.
- 9.In terms of OSHA, on outside side panel,there is built-in grounding static connector for easy grounding.



Horizontal Drum Storage Cabinet WA810550H

Volume (Gal/L)	Certification	Door type	Ext dimension (H×W×D/cm)	Packing dimension (H×W×D/cm)	Adjustable Shelves(Pcs)	N.W. (Kgs.)	G.W. (Kgs.)	Model
55/207	CE	Double Door/ Manual	127x76x121.9	145x88x140	-	146.2	168	WA810550H

WA810550H



Product details




Adjustable shelves with anti-leakage design




Shelf bracket welded on both sides of cabinet




FM Approved Anti-Static Device: Conductor grip combine the equipment with the cabinet to conduct the static to earth, thus to prevent fire accident



18Ga(1-mm) quality galvanized steel Unleaded coating with polish surface, which is corrosion and moisture proof



Fireproofing vents to effectively reduce the concentration of volatile substances, and prevent fire hazards. Special spill-proof shelves to avoid chemical leakage by accident.



The cabinet has three-point linkage lock, and the door can open 180°



The three-point bullets: Anti-static design structure



Two person management in line with Hazardous Chemicals Control Ordinance (December 1st, 2011 Version)